

68M Series

Sealed Wire Terminal

Offers Multiple Extension
Connections for One or Two
Digital Voice (or POTS) Lines


Equipped with Integral
Sealed Test Points

Utilizes Tii's Gel Sealed Tool-Less
IDC Rocker Design

Mounts Easily to a Suitable
Flat Surface or Installs in a Wire
Terminal Housing

CAT-6 Compliant

Listed to UL 1863



68M-01

The 68M Series Sealed Wire Terminal is designed for applications requiring more than one parallel connection (extension) to single or two pair service.



Tii Technologies Inc.

Corporate Headquarters:

141 Rodeo Drive
Edgewood, NY 11717
Phone: 631.789.5000 • Fax: 631.789.5063
Toll Free: 888.844.4720
sales@tiitech.com

Locations:

South March
Long March Industrial Estate
Daventry, Northamptonshire, NN11 4PH, UK
Phone: +44 (0) 1327 301853
Fax: +44 (0) 1327 879532
sales@tiitech.co.uk

Av. José de Escandón y Helguera
No. 21 Ciudad Industrial
Matamoros, Tamaulipas, C.P. 87494, México
Phone: 868.812.8011 • Fax: 868.812.8025
salesmx@tiitech.com.mx


KEY PRODUCT BENEFITS

- ▶ Incorporates integral sealed test points – no additional loose test clips required
- ▶ Accommodates multiple extension connections for one or two line digital voice (or POTS) signals
- ▶ Terminations are made to gel sealed insulation displacement contacts (IDC) by means of convenient tool-less rocker assemblies. Wire stripping is not required
- ▶ Compact, low profile design fits into applications where space is limited
- ▶ The Tii 68M Series may be mounted via screws to a suitable flat surface or installed within a Tii indoor/outdoor wire terminal housing
- ▶ Accepts 26 through 22 gauge solid conductor wire sizes

INDUSTRY STANDARDS

- ▶ Listed to cUL and UL 1863

68M Series



Dimensions are in Inches

ORDERING INFORMATION

Model No.	Description
68M-1	1 Pair Input, 11 Parallel Pair Output, Sealed Wire Terminal with Integral Sealed Test Points
68M-2	2 Pair Input, 2 Individual 5 Pair Outputs, Sealed Wire Terminal with Integral Sealed Test Points