## **761T Series**

Flush Mount Indoor Phone Jack Plate for Traditional Telco Applications

For Providing Telephone Connections Through RJ-11 Jack

Two Conductor IDC Terminations

Single Rocker Assembly for Simple and Reliable Connections

Low Contact Resistance

No Attenuation to Telephone Signals



Corporate Headquarters:

141 Rodeo Drive Edgewood, NY 11717 Phone: 631.789.5000 Fax: 631.789.5063 Toll Free: 888.844.4720 sales@tiitech.com




761S-2T


The 761 series flush mount indoor phone jack plate is designed to provide convenient RJ11 connectivity with IDC termination in the back and utilizes Tii's proprietary gel filled IDC rockers for wire terninations. The IDC rockers are color coded for tip and ring wire orientations. Termination of wires is easy as the wires do not need stripping. All one needs is to lift the rocker, straighten ends of the wire, insert and pull the rockers in fully down posistion.


#### **KEY PRODUCT BENEFITS**

- ► The 61 is a standard wall plate sized device and can be located at any telephone iack location
- Dual conductor gold plated RJ-11 jack for reliable RJ-11 connection
- Tool-less IDC rocker for telephone wire connections on the back side of jack plate
- All contacts are rated for 1.5 Amp max current
- IDC rockers are gel-filled for long term reliable connections

# **761T Series**







Dimensions are in Inches

### **SPECIFICATIONS**

Operating Voltage Range	40-60 Volts DC
Ringing Voltage	60-90 Volts AC
IDC Termination Gauge	#26-22
Operating Temperature	-40 to 60° C
Current Rating	1.5A Max.
Dielectric Withstand Voltage	1000 V Min.
Insulation Resistance	>100 Megohms
Contact Resistance	< 50 Megohms

### **ORDERING INFORMATION**

Model No.	Description
761( )-1T	Wall Plate with a Single RJ-11 Jack and a Singer Rocker Assembly
761( )-2T	Wall Plate with a Single RJ-11 Jack and a Dual Rocker Assembly
761( )-3T	Wall Plate with Dual RJ-11 Jacks and a Single Rocker Assembly
761( )-4T	Wall Plate with Dual RJ-11 Jacks and a Dual Rocker Assembly
761( )-5T	Wall Plate with Dual RJ-11 Jacks and 2 Single Rocker Assemblies
761( )-6T	Wall Plate with Dual RJ-11 Jacks and 2 Dual Rocker Assemblies
761-1T-14	Wall Plate with Single RJ-14 Jack and 2 Single Rocker Assemblies

Please insert "S" in place of ( ) S designates a sealed RJ-11 jack