Time is too valuable...choose Tii
Cost-effective solutions for project plans and budgets that can't afford long lead times.

Customer Connection Point Series (CCP) Fiber Wall Terminals

	CCP1	CCP2	CCP3	CCP5	CCP6	CCP7
Adapters Type	SC, SC-APC or LC	1 port SC, SC-APC, 2 ports LC	SC, SC-APC	SC	SC. SC-APC, Coax, RJ-45 , RJ-11	SC-APC - LC
Port Count	1 or 2	1 or 2	1 or 2	1	1 or 2	1 or 2
Mounting	Indoor Wall	IndoorWall / Baseboard	Indoor Wall / Electrical Box	Indoor Wall / Electrical Box	Indoor Wall / Electrical Box	Indoor Wall / Electrical Box
Dimensions (H x W x D)	3.9" x 3.3" x 0.8" (3.9" x 3.3" x 0.6" without tray)	3.0" x 5.8" x 0.6"	6.16" x 3.71"x 1.08"	2.8" x 4.5" x 0.81" with wallplate, 1.89" x 3.58" x 0.56"without wallplate	4.52" x 2.78" x 1.27"	4.5" x 3.3" x 0.7"
Markets	FTTP, FTTD, MDU	FTTP, MDU	FTTP, MDU, PON	FTTP, MDU, PON	FTTP, MDU, DOT	FTTP, MDU, PON
Splice	2 x 40mm	Accommodates up to 4.8mm fiber	2 x 40mm	–	–	One: Fusion or Fibrlok™
Available with Factory Loaded Pigtails	Yes	Yes	Yes	No	No	No
Key Product Benefits	• Compact design can terminate up to 2 fibers • Ideally used as an access point for MDU and FTTH ONTs as well as FTTD • Direct termination or fusion splice configurations • Multiple cable entry options • Available with factory loaded pigtails • Separate splice tray door with slack storage • Brownfield • Hinged top cover with hex lock screw	• Compact design can terminate up to 2 fibers • Ideally used as an access point for MDU point-of-entry • Direct termination or fusion splice configurations • Multiple cable entry options • Available with factory loaded pigtails • Greenfield and Brownfield • Tii FPS Series Fiber Pathway compatible • Flexible mounting options: o Wall o Single-gang wall box	• Compact design can terminate up to 2 fibers • Ideally used as an access point for MDU and FTTH ONTs as well as FTTD • Direct termination or fusion splice configurations • Multiple cable entry options • Available with factory loaded pigtails • Greenfield and Brownfield • Flexible mounting options: o Wall o Single-gang wall box	• Compact design can terminate up to 2 fibers • Ideally used as an access point for MDU and FTTH ONTs as well as FTTD • SC-APC interface with optional internal laser safety shutter • Multiple cable entry points • Greenfield and Brownfield • Tii FPS Series Fiber Pathway compatible • Flexible mounting options: o Wall o Baseboard o Wall plate mount	• Ideally used as an access point for MDU and FTTH ONT • Provisions for fiber management and slack storage • SC-APC interface with optional internal laser safety shutter • Secondary Keystone/SpeedStar port for optional connections such as coax, RJ-45 or RJ-11 • Multiple cable entry points • Greenfield and Brownfield • Tii FPS Series Fiber Pathway compatible • Flexible mounting options: o Wall o Baseboard o Wall plate mount	• Optionally enables ONT mounting • Supports field termination, fusion (2x) or mechanical splice using Fibrlok™ Model 2529 • Shuttered SC-APC or LC-UPC adapter prevents contamination • Multiple cable entry options: rear, bottom, sides • Greenfield and Brownfield • Tii FPS Series Fiber Pathway compatible • Flexible mounting options: o Wall o Baseboard o Wall plate mount
Industry Standards	cUL Listed to 1863,TIA/EIA604-3-A, IEC61754-4	cUL Listed to 1863,TIA/EIA604-3-A, IEC61754-4	cUL Listed to 1863,TIA/EIA604-3-A, IEC61754-4	cUL Listed to 1863,TIA/EIA604-3-A, IEC61754-4	cUL Listed to 1863,TIA/EIA604-3-A, IEC61754-4	cUL Listed to 1863,TIA/EIA604-3-A, IEC61754-4