



*Time is too valuable...choose Tii's Fiber Entrance Terminal Series.
A cost-effective solution for project plans and budgets
that can't afford long lead times.*

Fiber Entrance Terminal Series

FET1G Series



FET2G Series



FET3G Series



FET4G Series



SHF/FET Series Preterminated Stub Housings



Adapter Type	SC or LC (UPC/APC)	SC or LC (UPC/APC)	SC or LC (UPC/APC)	SC or LC (UPC/APC)	SC or LC (UPC/APC)
Port Count	*1 or 2 Single Cables	*6, 8, 12, 16	*4, 8, 12, 16, 24 (36, LC)	*12, 24, 36, 48	* Port Count is per FET unit
Mounting	Indoor/Outdoor Wall	Indoor/Outdoor Wall or Pole	Indoor/Outdoor Wall or Pole	Indoor/Outdoor Wall or Pole	Indoor/Outdoor Wall or Pole
Dimensions (H x W x D)	**6.11" x 4.33" x 2.15"	**8.48" x 9.94" x 2.50"	**13.24" x 10.16" x 4.73"	**12.77" x 12.52" x 7.15"	** Dimensions per FET unit
Markets	FTTx, MDU, PON, CPE/Premise Wiring, DOT, Wireless	FTTx, MDU, PON, CPE/Premise Wiring, DOT, Wireless	FTTx, MDU, PON, CPE/Premise Wiring, DOT, Wireless	FTTx, MDU, PON, CPE/Premise Wiring, DOT, Wireless	FTTx, MDU, PON, CPE/Premise Wiring, DOT, Wireless
Applications	A compact, patch and splice enclosure designed to provide a demarcation and transition point between fiber drop cable and the customer premise fiber cable	A compact enclosure designed to provide a demarcation and transition point between fiber drops and downstream devices. Its optional copper connectivity makes it an ideal device for interfacing to the Customer Premise, Small Cells, DAS, or G.fast modem devices	A compact fiber demarcation unit which features connectivity between the OSP fiber drops and customer fiber drops, allows for multiple splice and slack storage	A compact fiber demarcation unit which features connectivity between the OSP fiber drops and customer fiber drops, allows for multiple splice and slack storage	Stubbed FET units are available with pre-terminated cables. Stubbed enclosures enable fast termination to other hardware in or outside of buildings, by just pulling off the reel
Features	Compact, low profile design for applications where space is limited, external ground included, available with pigtailed	Compact low profile design; available with external ground, pigtailed and PLC splitters	Compact weatherproof design available with external ground, pigtailed, splicing capabilities and PLC splitters	Compact weatherproof design Available with external ground, pigtailed, splicing capabilities and PLC splitters	Factory terminated cable stub, Compact superior materials capable of withstanding harsh outdoor environments, including UV degradation, chemical exposure, and extreme temperature
Splice Capability	2 splice provisions when used w/ Tii FP01 adapter plate	Patch or splice, single or mass fusion	Patch or splice, single or mass fusion	Patch or splice in cassettes - single fusion or MPO input cassettes	-
Slack Storage	No	Yes	Yes	Yes	-
Lockable	No	Yes	Yes	Yes	Yes
Splitters	No	1X4, 1X8	1X4, 1X8, 1X16	Yes - Tii PLC9	No
Industry Standards	Meets GR-771 Requirements	Meets GR-771 Requirements	Meets NEMA-4, GR-771 and GR-2898 Requirements	Designed to NEMA-4 and GR-2898 Requirements	Meets GR-771 Requirements